

Preventative Maintenance Checklist

F			I		
Frequency	Preventative Maintenance	Item	Completed by	Date	Order Link
Daily	Clean the door gasket with a wet cloth and check for wear - Replace if necessary. Clean all external surfaces with Optim1 disinfectant. Completely empty the waste tank every time you refill the water reservoir. If using a data logger, transfer the data on the USB drive to your computer.	OPTIM1 WIPE ON THE PROPERTY OF THE PROPERTY O			Optim1 6"x7" Wipes Bravo 17V Chamber Drain Filter
	Clean chamber drain filter.				
Weekly	Clean the chamber and appropriate accessories with a wet cloth. If required, use a neutral detergent (a mild detergent containing no alkalies or bleaches). Carefully rinse with distilled water and remove any residue. Clean the internal (and external - if installed) water tank with Opticlave Autoclave Cleaner.	PTI CLAVE. JUDICAN CLEANE AUTOLAN CLEANE AU			
	Inspect, clean, or replace the drain filter.				Stat Dri Products Opti-Clave 32oz
	Ensure area around Bravo is dust free.				
Monthly	Test the safety valve located on the back of the unit.	STATINUS AJOS			
3 - 6 Months	Or every 500 Cycles replace the Biological Filter.				
Yearly	Replace the Door Gaset every 1000 cycles or 12 months (whichever is first).				Bravo 17V Biological Filter Bravo 17V Door Gasket
General	If printer paper is not printing properly, remove paper, tighten the paper around the roll and retry.	TANK OF THE PROPERTY OF THE PR			
	Complete Bravo 17V PM Kit available includes: Door Gasket, Biological Filter, and Chamber Drain Filter				Bravo 17V QPM Kit Bravo 17V Thermal Paper



Scican Bravo 17V

